

Intelligent Addressable Smoke & Heat Detector



1 Feature and Benefits

- EN54-29 Compliance
- Using microprocessor technology with memory capacity up to 10 events
- Analogue sending and digital addressing
- Provide real time algorithm to the control panel
- Smart linear drift compensation
- 360 degree visual indicator
- Onsite Adjustable Parameter
- Removable chamber against dust and small insect
- Ancillary remote indicator output
- Aesthetically pleasing design

2 Technical Specification

- | | |
|-------------------------|--|
| ● Listed | LPCB Pending |
| ● Compliance | EN54-29 |
| ● Input Voltage | 24VDC [16V to 28V] |
| ● Current Consumption | Standby 0.6mA, Alarm: 4mA |
| ● Protocol/Addressing | TNA, Value range from 1 to 254 |
| ● Smoke Sensitivity | As per stipulated standard |
| ● Heat Class Type | A2R |
| ● Indicator | Single LED / 360 degree Visual |
| ● Material / Colour | ABS / White Glossy finishing |
| ● Dimension / Height | Diameter 99.7 mm / 57 mm |
| ● Weight | 145g (with Base), 90g (without Base) |
| ● Operating Temperature | -10°C to +50°C |
| ● Humidity | 0 to 95% Relative Humidity, Non condensing |

