

Addressable Input Module



1 Feature and Benefits

- EN54-18 Compliance
- Built-in MCU processor and digital addressing
- Fire or Supervisory signal configuration
- Input cable monitored
- Normally open configuration
- LED status indicator
- Loop powered device
- Aesthetically pleasing design
- Surface mounting with fix base for simple installation

2 Technical Specification

- | | |
|-----------------------------|---|
| ● Listed | LPCB Pending |
| ● Compliance | EN54-18:2005/AC2007 |
| ● Input Voltage | 24VDC [16V to 28V] |
| ● Current Consumption | Standby 0.6mA, Alarm: 1.0mA |
| ● Protocol/Addressing | TNA, Value range from 1 to 254 |
| ● Input Relay | Normally Open dry contact |
| ● Input Resistance | 5.1Kohms/ ¼ W |
| ● Indicator Status | Normal: Single blink/Active: Steady/Fault: Double Blink |
| ● Material / Colour | ABS / White Glossy finishing |
| ● Dimension / LWH | 108 mm x 86 mm x38 mm |
| ● Weight | 155g (with Base), 85g (without Base) |
| ● Operating Temperature | -10°C to +50°C |
| ● Ingress Protection Rating | IP30 |
| ● Humidity | 0 to 95% Relative Humidity, Non condensing |