

LCD Repeater Panel



1 Feature and Benefits

- EN54-2 Compliance
- Fire display passive repeater panel
- Built-in MCU processor and digital addressing
- Fast response of audible and visible signal from the panel
- Direct access common keys such as MUTE, UP, DOWN and BROWSE.
- Programmable Zone Display such as All Zone, Single Zone and Three Adjacent Zone
- LED status indicator
- Onsite Adjustable Parameter
- Loop sited wiring with external 24V supply
- Surface mounting with fix base for simple installation

2 Technical Specification

- | | |
|-------------------------|--|
| ● Compliance | EN 54-2: 1997+A1: 2006 |
| ● Input Voltage | Loop Power: 24VDC [16V to 28V]
External PSU: 24VDC [20 to 28V] |
| ● Current Consumption | Loop: Standby: 1mA, Alarm: 1.2mA
External PSU: Standby: 25mA, Alarm: 80mA |
| ● Memory Capacity | Up to 300 fire event history |
| ● Number per loop | Up to 254 units (ideal) |
| ● Material / Colour | ABS / White Glossy finishing |
| ● Dimension / LWH | 180mm x 110 mm x44 mm |
| ● Weight | 300g (with Base), 256g (without Base) |
| ● Operating Temperature | 0°C to +40°C |
| ● Humidity | 0 to 95% Relative Humidity, Non condensing |